

## 100 Series: Single-Size Pneumatic Pipe Plugs



Example: 100-12

PART #	SIZE RANGE	DIAMETER	LENGTH	WEIGHT	REQUIRED INFLATION PRESSURE	MAX ALLOWABLE BACK PRESSURE	
						AIR	WATER
100-4	3.5"-4.5"	3.5"	5.5"	1.5 lbs	25 psi	10 psi	25 ft
	90 mm-125 mm	90 mm	140 mm	0.67 kg	1.7 bar	0.69 bar	7.6 m
100-46	3.5"-6.5"	3.5"	9.5"	2.0 lbs	30 psi	10 psi	25 ft
	90 mm-175 mm	90 mm	241 mm	0.91 kg	2.1 bar	0.69 bar	7.6 m
100-6	5.0"-6.5"	5.0"	6.0"	3.0 lbs	25 psi	10 psi	25 ft
	125 mm-175 mm	125 mm	152 mm	1.4 kg	1.7 bar	0.69 bar	7.6 m
100-68	5.0"-8.5"	5.0"	14.0"	4.0 lbs	30 psi	10 psi	25 ft
	125 mm-225 mm	125 mm	356 mm	1.81 kg	2.1 bar	0.69 bar	7.6 m
100-8	7.0"-8.5"	7.0"	7.5"	5.0 lbs	25 psi	10 psi	25 ft
	175 mm-225 mm	175 mm	191 mm	2.3 kg	1.7 bar	0.69 bar	7.6 m
100-10	9.0"-10.5"	9.0"	10.0"	8.5 lbs	25 psi	10 psi	25 ft
	225 mm-275 mm	225 mm	254 mm	3.8 kg	1.7 bar	0.69 bar	7.6 m
100-12	11.0"-12.5"	11.0"	12.0"	12.5 lbs	25 psi	10 psi	25 ft
	275 mm-325 mm	275 mm	305 mm	5.6 kg	1.7 bar	0.69 bar	7.6 m
100-15	13.5"-15.5"	13.5"	15.0"	24.0 lbs	20 psi	10 psi	25 ft
	350 mm-400 mm	350 mm	381 mm	10.9 kg	1.4 bar	0.69 bar	7.6 m
100-18	16.5"-18.5"	16.5"	18.0"	33.5 lbs	20 psi	10 psi	25 ft
	425 mm-470 mm	425 mm	457 mm	15.5 kg	1.4 bar	0.69 bar	7.6 m
100-21	18.5"-21.5"	18.5"	21.0"	42.0 lbs	20 psi	8 psi	20 ft
	475 mm-550 mm	475 mm	533 mm	19.1 kg	1.4 bar	0.55 bar	6.1 m

125 Series  
Safety Inflation  
Rope/Hose  
Page 25



Pole & Attachment for  
Remote Placement  
Page 26



## 200 Series: Single-Size Pneumatic Pipe Plugs w/ Bypass



Example: 200-8-2

PART #	SIZE RANGE	DIAMETER	LENGTH	WEIGHT	BYPASS SIZE	REQUIRED INFLATION PRESSURE	MAX ALLOWABLE BACK PRESSURE	
							AIR	WATER
200-4-1	3.5"-4.5"	3.5"	8.0"	1.5 lbs	1"	25 psi	10 psi	25 ft
	90 mm-125 mm	90 mm	203 mm	0.67 kg	25.4 mm	1.7 bar	0.69 bar	7.6 m
200-6-1	5.0"-6.5"	5.0"	8.0"	3.0 lbs	1"	25 psi	10 psi	25 ft
	125 mm-175 mm	125 mm	203 mm	1.4 kg	25.4 mm	1.7 bar	0.69 bar	7.6 m
200-8-2	7.0"-8.5"	7.0"	10.0"	6.0 lbs	2"	25 psi	10 psi	25 ft
	175 mm-225 mm	175 mm	254 mm	2.7 kg	50.8 mm	1.7 bar	0.69 bar	7.6 m
200-10-3	9.0"-10.5"	9.0"	13.0"	10.5 lbs	3"	25 psi	10 psi	25 ft
	225 mm-275 mm	225 mm	330 mm	4.8 kg	76.2 mm	1.7 bar	0.69 bar	7.6 m
200-12-4	11.0"-12.5"	11.0"	15.0"	15.5 lbs	4"	25 psi	10 psi	25 ft
	275 mm-325 mm	275 mm	381 mm	7.0 kg	101.6 mm	1.7 bar	0.69 bar	7.6 m
200-15-4	13.5"-15.5"	13.5"	19.0"	27.5 lbs	4"	20 psi	10 psi	25 ft
	350 mm-400 mm	350 mm	483 mm	14.5 kg	101.6 mm	1.4 bar	0.69 bar	7.6 m
200-18-4	16.5"-18.5"	16.5"	21.0"	40.5 lbs	4"	20 psi	10 psi	25 ft
	425 mm-470 mm	425 mm	533 mm	18.4 kg	101.6 mm	1.4 bar	0.69 bar	7.6 m
200-21-4	18.5"-21.5"	18.5"	24.0"	48.5 lbs	4"	20 psi	8 psi	20 ft
	475 mm-550 mm	475 mm	610 mm	22.0 kg	101.6 mm	1.4 bar	0.55 bar	6.1 m

125 Series  
Safety Inflation  
Rope/Hose  
Page 25



Pole & Attachment for  
Remote Placement  
Page 26

