



TYPE 26 (6 bar / 87 psi,
12 bar / 435 psi)

HIGH-PRESSURE PLUGS - PLUGY HP 6 bar (87 psi), 12 bar (174 psi) AND 30 bar (435 psi)

1. 15.



SAVA PLUGY HP plugs are specially reinforced plugs suitable for sealing of pipes with extremely high back pressures.

Special reinforcement

High back pressures

Heavy duty

PLUGY HP 6 bar (435 psi)
350 - 500 (14"-20")
60909



PLUGY HP 6 bar (87 psi), **12 bar** (174 psi)

PLUGY HP 30 bar (435 psi) **DESIGN**



PLUGSY HP 30 bar (435 psi)
537323



Front view

ACCESSORIES 6 bar (87 psi) AND 12 bar (174 psi)



SINGLE FITTING CONTROLLER,
0.9 kg (2 lbs)
12 bar (174 psi) 531544
6 bar (87 psi) 531542



INFLATION HOSE, RED
10 m (33')
1.2 kg (2.6 lbs)
74268



INFLATION HOSE, BLUE
10 m (33')
1.2 kg (2.6 lbs)
71248



INFLATION HOSE, YELLOW
10 m (33')
1.2 kg (2.6 lbs)
76686



POLY LIFT INFLATION HOSE,
5 m (16.4'),
1.9 kg (4.2 lbs)
60957



POLY LIFT INFLATION HOSE,
10 m (33'),
2.4 kg (5.3 lbs)
60958

HIGH-PRESSURE PLUGS – PLUGY HP 6 bar (87 psi), 12 bar (174 psi) AND 30 bar (435 psi)



TYPE 26 - SAFETY
(30 bar / 435 psi)

1. 15.

ACCESSORIES 30 bar (435 psi)



SINGLE FITTING CONTROLLER,
0.9 kg (2 lbs)
30 bar (435 psi)
282184



INFLATION HOSE,
10 m (33'),
4 kg (8.8 lbs)
546714

PLUGY HP 6 bar (87 psi) - BLOCKING PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE [bar] / [psi]	MAX. ALLOWED BACK PRESSURE [bar] / [psi]	DEFLATED PLUG		PRODUCT WEIGHT [kg] / [lbs]	EYE BOLT M THREAD	INFLATION VALVE THREAD SIZE
		MIN. DIA. [mm] / [inch]	MAX. DIA. [mm] / [inch]			DIAMETER [mm] / [inch]	LENGTH [mm] / [inch]			
60887	100-150 / 4"-6"	100 / 4"	150 / 6"	6 / 87	3 / 44	92 / 3.6"	535 / 21"	1.2 / 3	6	R 1/4"
60907	150-200 / 6"-8"	150 / 6"	200 / 8"	6 / 87	3 / 44	142 / 5.6"	575 / 23"	2 / 5	8	R 1/4"
60908	200-300 / 8"-12"	200 / 8"	300 / 12"	6 / 87	3 / 44	192 / 7.6"	635 / 25"	3.2 / 7	8	R 1/4"
60909	350-500 / 14"-20"	350 / 14"	500 / 20"	6 / 87	3 / 44	322 / 12.7"	865 / 34"	8.7 / 20	8	R 1/4"
60924	500-600 / 20"-24"	500 / 20"	600 / 24"	6 / 87	3 / 44	472 / 18.6"	1185 / 47"	18 / 40	10	R 1/4"

PLUGY HP 12 bar (174 psi) - BLOCKING PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE [bar] / [psi]	MAX. ALLOWED BACK PRESSURE [bar] / [psi]	DEFLATED PLUG		PRODUCT WEIGHT [kg] / [lbs]	EYE BOLT M THREAD	INFLATION VALVE THREAD SIZE
		MIN. DIA. [mm] / [inch]	MAX. DIA. [mm] / [inch]			DIAMETER [mm] / [inch]	LENGTH [mm] / [inch]			
518561	100-125 / 4"-5"	100 / 4"	125 / 5"	12 / 174	10 / 145	92 / 3.6"	540 / 21"	1.5 / 4	6	R 1/4"
518562	150 / 6"	150 / 6"	150 / 6"	12 / 174	10 / 145	142 / 5.6"	580 / 23"	2.7 / 6	8	R 1/4"
518563	200-250 / 8"-10"	200 / 8"	250 / 10"	12 / 174	10 / 145	192 / 7.6"	640 / 25"	4.3 / 10	8	R 1/4"
518564	300-350 / 12"-14"	300 / 12"	350 / 14"	12 / 174	10 / 145	272 / 10.7"	670 / 27"	8 / 18	8	R 1/4"
518565	400 / 16"	400 / 16"	400 / 16"	12 / 174	10 / 145	322 / 12.7"	870 / 34"	11.5 / 26	10	R 1/4"
518566	500 / 20"	500 / 20"	500 / 20"	12 / 174	10 / 145	472 / 18.6"	1190 / 47"	24.1 / 53	10	R 1/4"

PLUGY HP 30 bar (435 psi) - BLOCKING PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE [bar] / [psi]	MAX. ALLOWED BACK PRESSURE [bar] / [psi]	DEFLATED PLUG		RUBBER SLEEVE LENGTH [mm] / [inch]	PRODUCT WEIGHT [kg] / [lbs]
		MIN. DIA. [mm] / [inch]	MAX. DIA. [mm] / [inch]			DIAMETER [mm] / [inch]	LENGTH [mm] / [inch]		
538625	55-75 / 2"-3"	55 / 2"	75 / 3"	30 / 435	16 / 232	54 / 2.1"	615 / 24"	400 / 16"	3 / 7
53837	75-100 / 3"-4"	75 / 3"	100 / 4"	30 / 435	16 / 232	73 / 2.9"	600 / 24"	400 / 16"	5 / 11
53838	100-150 / 4"-6"	100 / 4"	150 / 6"	30 / 435	16 / 232	88 / 3.5"	614 / 24"	400 / 16"	6.7 / 15
53839	150-200 / 6"-8"	150 / 6"	200 / 8"	30 / 435	16 / 232	122 / 4.8"	621 / 24"	400 / 16"	13 / 29

PLUGSY HP 30 bar (435 psi) - BYPASS PLUGS

PART NUMBER	NOMINAL SIZE	SIZE USAGE RANGE		REQUIRED INFLATION PRESSURE [bar] / [psi]	MAX. ALLOWED BACK PRESSURE [bar] / [psi]	FLOW THROUGH [mm] / [inch]	BYPASS THREAD [inch]	RUBBER SLEEVE LENGTH [mm] / [inch]	PRODUCT WEIGHT [kg] / [lbs]
		MIN. DIA. [mm] / [inch]	MAX. DIA. [mm] / [inch]						
537553	55-75 / 2"-3"	55 / 2"	75 / 3"	30 / 435	16 / 232	10 / 0.4"	3/8	400 / 16"	3 / 7
537661	75-100 / 3"-4"	75 / 3"	100 / 4"	30 / 435	16 / 232	15 / 0.6"	1/2	400 / 16"	4.8 / 11
537323	100-150 / 4"-6"	100 / 4"	150 / 6"	30 / 435	16 / 232	20 / 0.8"	3/4	400 / 16"	7 / 15
537672	150-200 / 6"-8"	150 / 6"	200 / 8"	30 / 435	16 / 232	25 / 1"	1	400 / 16"	13 / 29